"TEXTURES STONE" — HEAVY CONTRACT USE WATER-RESISTANT LVT

Product Definition		Dryback LVT
Embossing Type		Realistic
Surface Treatment		UV, ultra-matt finish
Scratch Resistance	ISO 1518-1	Value on application. Scratch-resistant aluminium oxide
Water Resistance		Highly water-resistant (unsuitable for wetrooms)
Dimensions		304.8 × 609.6mm (12 × 24")
Pack Size/Weight		16 tiles = 2.97m ² 13.6kg
Thickness / Wear Layer		2.50mm/0.55mm
Micro-bevelled Edges		4 × micro-bevels per plank
Performance Classification	EN ISO 10874	Class 33/42 Heavy Contract
Castor Chair Test	EN ISO 4918	Pass
Residual Indentation	EN ISO 24343-1	≤0.1mm
Anti-slip Classification	EN 16165:2021	36+ (denotes product as low risk)
Reaction to Fire	EN 13501-1	B _{fl} -s1
Resistance to Staining	ISO 26987	Pass
Reaction to Light	ISO 105 B02	≥6
Thermal Conductivity	EN 12667	0.051 m ² K/W
Thermal Resistance	EN 12667	0.039 m² K/W
Dimensional Stability	EN ISO 23999	≤0.15%
Curling Resultant to Heat	EN ISO 23999	≤1.0mm
UFH Suitability	Yes	Water-based UFH system only (max. temp 27°C/80.6F)
VOC Emissions	ISO 16000	A+
Formaldehyde HCHO Emission	EN 717-1	Class E1
Indoor Air Comfort	Eurofins	Pass — Gold
UKCA/CE/Floorscore		Certified
		30 year residential/15 year commercial





























GENERAL

Cleaning, maintenance and installation	Please refer to guidance at www.textureslvt.co.uk
Laying instructions	We strongly recommend fitting is carried out by flooring professionals only and that advice is sought regarding the surface on which the LVT is to be laid and the correct adhesives to be used.
Please note	The Textures™ Collection has colour variations between the tiles to accentuate and enhance the unique character of real stone flooring, specially developed to replicate the natural beauty of stone and marble.
Warranty	Textures [™] Stone Realistic Embossed LVT is backed by our 30-year Residential and 15-year Commercial Warranty, subject to T&Cs (available on request) and are downloadable at www.textureslvt.co.uk